

Safety Data Sheet

ISSI

Binary UniCoat Pressure Sensitive Paint (BUNC-12)

Version 1.0/Revision Date 5/3/2018

Section 1. Product and Company Identification

Product name: Binary UniCoat Pressure Sensitive Paint (BUNC-12)
Recommended Use: Paint
Company: Innovative Scientific Solutions, Inc. (ISSI)
7610 McEwen Road
Dayton, Ohio, 45459 USA
Telephone: +1-937-630-3012
Emergency Telephone Number: +1-800-535-5053 (INFOTRAC)

Section 2. Hazards Identification

Signal Word: **WARNING**
Hazard Statement: Flammable Liquid, Target Organ Effect
Target Organs: Central nervous system
Precautionary Statements:
Keep this flammable material away from heat, sparks, flames, or other sources of ignition.
The fumes of this product are harmful and should not be inhaled.
This product is not to be consumed.



Section 3. Hazardous Components Information

| | | |
|--------------------------------|-----|------------|
| Acetone | 17% | 67-64-1 |
| Methyl Methacrylate | 7% | 80-62-6 |
| n-Butyl Methacrylate | 5% | 97-88-1 |
| Aromatic Petroleum Distillates | 4% | 64742-94-5 |
| Toluene | 2% | 108-88-3 |

Section 4. First Aid Measures

- **Inhalation:** Remove person to fresh air. Seek medical attention.
- **Skin Contact:** Wash off with soap and water. Seek medical attention.
- **Eye Contact:** Flush eyes with water for 15 minutes. Seek medical attention.
- **Ingestion:** Seek medical attention.

Section 5. Fire Fighting Measures

- **Flammable Properties**
Flash Point: -20° C (-4° F) closed cup
Ignition Temperature: No data available.
- **Extinguishing Media** Dry chemical or CO₂
- **PPE for Firefighters** Self-contained breathing apparatus
- **Further Information** Use water spray to cool unopened containers

Safety Data Sheet



Binary UniCoat Pressure Sensitive Paint (BUNC-12)

Version 1.0/Revision Date 3/12/2015

Section 6. Accidental Release Measures

- **Personal Precautions:** Avoid breathing fumes. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safety. Vapor can accumulate to form explosive concentrations especially in low areas.
- **Environmental Precautions:** Avoid discharge into the environment by preventing the product from entering sewer drains or storm drains.
- **Methods for Cleaning Up Spills:** Use noncombustible absorbent material such as vermiculite or sand to absorb the spill. After the absorbent is dry dispose of it in accordance with local regulations.

Section 7. Handling and Storage

The container should be stored in a cool, dry place away from sources of ignition (sparks, flame, etc.). Avoid areas where static charge can build which could ignite the product (carpet). Store this product away from strong oxidizing agents.

Section 8. Exposure Control Personal Protection

- **Respiratory:** Use full face respirator that is for organic vapors and is properly fitted to the end user if the product is used where ventilation is unavailable. Self-contained breathing apparatus or a suitable exhaust hood are recommended.
- **Hand Protection:** Use protective gloves.
- **Eye Protection:** Safety glasses.
- **Hygiene Measures:** Practice good industrial hygiene and safety by washing hands thoroughly with soap and water after using this product.

Section 9. Physical and Chemical Properties

| | |
|----------------------------|------------------------------|
| Appearance: | Aerosol |
| Odor: | Characteristic |
| Odor Threshold: | No data |
| Vapor Pressure: | N/A |
| Vapor Density: | No data |
| pH: | N/A |
| Melting Point: | No data |
| Boiling Point: | 133° C (271.4° F) at 760mmHg |
| Flash Point: | -20° C (-40° F) |
| Evaporation Rate: | No data |
| Ignition Temperature: | No data |
| LEL: | No data |
| UEL: | No data |
| Auto Ignition Temperature: | No data |
| Decomposition Temperature: | No data |
| Viscosity: | N/A |
| Partition Coefficient: | N/A |
| Specific Gravity: | 1.57 |
| Water Solubility: | N/A |

Safety Data Sheet



Binary UniCoat Pressure Sensitive Paint (BUNC-12) Version 1.0/Revision Date 3/12/2015

Section 10. Stability and Reactivity

- **Storage:** Stable under recommended storage conditions.
- **Conditions to Avoid:** Heat, flames, sparks
- **Materials to Avoid:** Strong oxidizing agents
- **Hazardous Decomposition Products:** carbon monoxide and carbon dioxide
- **Hazardous Reactions:** Can form an explosive mix with air

Section 11. Toxicological Information

No data

Section 12. Ecological Information

Elimination: No data available

Unprofessional or irresponsible use or disposal of this product could pose a long term danger to the environment.

Section 13. Disposal Considerations

Observe all local waste disposal regulations and contact a licensed, professional waste disposal service to dispose of this product.

Section 14. Transport Information

Proper Shipping Name: Aerosols
USDOT Hazard Class 2 Flammable Gas
UN 1950

Section 15. Regulatory Information

OSHA Hazards: Flammable Liquid, Target Organ Effect

Section 16. Additional Information

The above information is believed to be correct by ISSI personnel based on present knowledge but is intended solely as a guide. Always take precautions and behave professionally and responsibly when handling chemicals. ISSI assumes no liability whatsoever for improper handling, storage, or utilization outside of the intended use of this product. 3/12/2015